

SUAY70 高温压力变送器

SUAY70

—

-40

380

PN

 β 

450-850

适用范围

产品特点

- -40~380
- -100KPa~0...100KPa...260MPa
- -
-
-

产品性能指标

/	-100KPa~0...10KPa...1MPa...260MPa						
	316						
	±0.15%FS		±0.25%FS		±0.5%FS		±1%FS
	4-20mA 0-5V 0-10V 1-5V HART				12-30VDC 24VDC		
	0.5-4.5V				5VDC/12-30VDC 24VDC		
	RS485				5VDC/5-16VDC/24VDC		
	-40 125	-40 150	-40 200	-40 250	-40 380	0 800	
-20 80	-20 130	0 150	0 200	0 200	0 200		
-40 100							

	$\pm 0.1\%FS/$ $\pm 0.02\%FS/$ $\pm 0.02\%FS/$ 60MPa 2 10^6 P:10-90%FS 20g IEC 60068-2-6 20g 11mS $\leq 2ms$ 10^{-5} $\leq U-12 / 0.02 \Omega$ $> 100K\Omega$ 200M Ω 100VDC M20*1.5 ; G1/2 G1/4 2m 304/316L IP65 IP67 Ex ia CT6 400	
--	--	--

选型参数对照表

SUAY70	-100KPa~0 ...10KPa ...100MPa	3.±0.15%FS 2:±0.25%FS 1:±0.5%FS 0:±1%FS	A1:4-20mA V1:0-5V V2:1-5V V3:0-10V V4:0.5-4.5V D:RS485 V0:	M1:M20*1.5 M2:G1/4 M3:G1/2 M0:	N1: 2 N2: N3:	S: F: L: E: T1:125 T2:150 T3:200 T4:250 T5:380 T6:800 ()
SUAY70.1.A1.M1.N1.T2						

选型提示：

- 1.
2. “ E ”
- 3.