

SUAY20 通用液位变送器

SUAY20

MEMS



适用范围

产品特点

-
- IP68
-
-
-
-

产品性能指标

/	0-1mH ₂ O...200mH ₂ O 0-20mH ₂ O 0-2mH ₂ O		
	4-20mA 0-5V 1-5V 0-10V	12-30VDC(24VDC)	
	0.5-4.5V	5VDC/12-30VDC(24VDC)	
	RS485	5VDC/12-30VDC(24VDC)	
	316 ±0.1%FS ±0.25%FS ±0.5%FS		

-20	80
-10	70
-40	100
$\pm 0.1\%FS/$	
$\pm 0.02\%FS/$	
$\pm 0.02\%FS/$	
$\pm 0.2\%FS/$	
$\pm 0.05\%FS/$	
$\pm 0.05\%FS/$	
2	
10^6	P:10-90%FS
$\leq 1ms$	
10^{-5}	
$\leq U-12$	/0.02 Ω
$>100K\Omega$	
200M Ω	100VDC
/	/ M20*1.5 G1/2 DN2
$\Phi 7.2mm$	
304/316L	
IP68	
Ex ia	CT6
316L	
500	

选型参数对照表

SUAY20	0-1mH ₂ O ...200mH ₂ O	4:±0.1%FS 2:±0.25%FS 1:±0.5%FS	A1:4-20mA V1:0-5V V2:1-5V V3:0-10V V4:0.5-4.5V D:RS485 V0:	M1:M20*1.5 M2:G1/4 M3:G1/2 M5:DN20 M0:	N1: 2 N2:HSM N4:IP68 N5: IP68	F: B: L: E:
SUAY20. 2. A1. N4. E						

选型提示：

- 1.
2. “ E ”
- 3.