

SUAY41 差压变送器

SUAY41

316L

适用范围

产品特点

- T
-
-
-

产品性能指标

0~1KPa...40MPa

316

±0.1%FS ±0.15%FS ±0.25%FS ±0.5%FS

/ 4-20mA 0-5V 0-10V 1-5V 12-30VDC 24VDC

0.5-4.5V 5VDC/12-30VDC 24VDC

RS485

5VDC

	±0.1%FS/	±0.2%FS/
	±0.02%FS/	±0.05%FS/
	±0.02%FS/	±0.05%FS/
	10 ⁶	P:10-90%FS
20g	IEC 60068-2-6	
20g	11mS	
≤1ms		
	10 ⁻⁵	
≤	U-12 /0.02 Ω	>100KΩ
200MΩ	100VDC	
M20*1.5	G1/4	G1/2
		2m
304/316L		
IP65		IP67
Ex ia	CT6	
	316L	
400		

选型参数对照表

SUAY41	0~1KPa ...40MPa	4:±0.1%FS 3:±0.15%FS 2:±0.25%FS 1:±0.5%FS	A1:4-20mA V1:0-5V V2:1-5V V3:0-10V V4:0.5-4.5V D:RS485 V0:	M1:M20*1.5 M2:G1/4 M8: M3:G1/2 M0:	N1: 2 N2: N3:	S: L: E:
SUAY41.2.A1.M8.N1.E						

选型提示：

- 1.
2. " E "
- 3.